

# CT79 CT79E




Wet tantalum capacitors  
**Hermetically sealed tantalum cases**  
 Axial leads  
 Polarized

## ELECTRICAL AND CLIMATIC CHARACTERISTICS

	CT79	CT79E
Detail specification	CECC 30202-801 - CECC 30202-005 - CECC 30202-001	CECC 30202-801 - CECC 30202-005 - CECC 30202-001
	According to MIL-PRF-39006/22	According to MIL-PRF-39006/25
	ESCC 3003/005	ESCC 3003/005
	ESA/ESCC EPPL2	ESA/ESCC EPPL2
Operating temperature	-55°C +125°C	-55°C +125°C
Damp heat	56 days	56 days
Capacitance range	1,7µF ⇔ 1200µF	5,6µF ⇔ 2200µF
Tolerance	±10% - ±20%	±10% - ±20%
Voltage range	6V ⇔ 125V	6V ⇔ 150V
Max. capacitance change -55°C	see table	see table
Max. capacitance change +85°C	see table	see table
Max. capacitance change +125°C	see table	see table
Maximum DF at +20°C	see table	see table
Maximum DF at +85°C	= lim20°C	= lim20°C
Maximum DF at +125°C	= lim20°C	= lim20°C
Max. impedance (100Hz) at -55°C	see table	see table
Max. leakage current at +20°C	see table	see table
Max. leakage current at +85°C	see table	see table
Max. leakage current at +125°C	= lim+85°C	= lim+85°C
Max. ripple current 40kHz +85°C	see table	see table
Max. Reverse voltage at +20°C	3 volts	3 volts
Max. Reverse voltage at +85°C	3 volts	3 volts
Max. Reverse voltage at +125°C	3 volts	3 volts
Max. surge voltage at +85°C	1,15 x U <sub>R</sub>	1,15 x U <sub>R</sub>
Max. surge voltage at +125°C	1,15 x U <sub>C</sub>	1,15 x U <sub>C</sub>

## DIMENSIONS (mm)

Case code	Dimensions with insulating sleeve		
	L max	D max	d +10% -0,05
A	18	5,6	0,6
B	23	7,4	0,6
C	26	10,1	0,6
D	34	10,1	0,6



**MARKING, PACKAGING, CONSTRUCTION:**  
 see general characteristics

## HOW TO ORDER

Commercial description	Model		Case	Capacitance in µF	Tolerance in %	DC Voltage	Termination
		CT79	CT79E	D	850µF	20%	25V
EXXELIA PN	Model code		Case	Capacitance code	Tolerance code	DC Voltage code	Termination
	TS79	TS79E	D	857	M	025	A
	Expressed in pF with 3 digits: 2 digits for the value and the third for the multiplier			K = 10% M = 20%	Expressed in volt with 3 digits	Commercial description H = SnPb (non RoHS) - = Sn100% (RoHS)	EXXELIA PN A = SnPb (non RoHS) F = Sn100% (RoHS)

# CT79

## CT79 SMD

[Standard range]

## STANDARD RATINGS - ELECTRICAL CHARACTERISTICS

Capacitance 100Hz +20°C ( $\mu$ F)	Case (code)	Type	Capacitance maximum change			Max. DF +20°C (%)	Max. Impedance 100Hz -55°C ( $\Omega$ )	Max. I leak		Irms Max. 40kHz +85°C (mA)	
			-55°C (%)	+85°C (%)	+125°C (%)			+20°C ( $\mu$ A)	+85°C ( $\mu$ A)		
<b>Rated voltage (+85°C) 6 V - 6,3 V - Category voltage (+125°C) 4 V</b>											
30	A	CT79	CT79 SMD	-40	+10	+12	9	100	1	2	820
68	A	CT79	CT79 SMD	-40	+14	+16	15	60	1	2	960
140	B	CT79	CT79 SMD	-40	+14	+16	21	40	1	3	1200
220	B	CT79	CT79 SMD	-44	+16	+18	36	30	1	6,5	1370
270	B	CT79	CT79 SMD	-44	+17	+20	41	25	1	6,5	1375
330	C	CT79	CT79 SMD	-44	+14	+16	36	20	2	7,9	1800
560	C	CT79	CT79 SMD	-64	+17,5	+20	50	25	2	13	1900
1000	D	CT79	CT79 SMD	-80	+25	+25	68	22	3	14	2388
1200	D	CT79	CT79 SMD	-80	+25	+25	86	20	3	14	2388
<b>Rated voltage (+85°C) 8 V - Category voltage (+125°C) 5 V</b>											
25	A	CT79	CT79 SMD	-40	+10,5	+12	7,5	100	1	2	820
56	A	CT79	CT79 SMD	-40	+14	+16	14	59	1	2	900
120	B	CT79	CT79 SMD	-44	+17,5	+20	20	50	1	2	1230
220	B	CT79	CT79 SMD	-44	+16	+18	37	30	1	7	1370
290	C	CT79	CT79 SMD	-64	+17,5	+20	34	25	2	6	1770
430	C	CT79	CT79 SMD	-64	+17,5	+20	46	25	2	14	1825
850	D	CT79	CT79 SMD	-80	+25	+25	60	22	3	16	2456
<b>Rated voltage (+85°C) 10 V - Category voltage (+125°C) 6,3 V</b>											
20	A	CT79	CT79 SMD	-32	+10,5	+12	6	175	1	2	820
47	A	CT79	CT79 SMD	-36	+14	+16	13	100	1	2	855
100	B	CT79	CT79 SMD	-36	+14	+16	15	60	1	4	1200
150	B	CT79	CT79 SMD	-32	+14	+16	28	45	1	7	1271
180	B	CT79	CT79 SMD	-35	+14	+16	29	40	1	7	1365
250	C	CT79	CT79 SMD	-40	+14	+16	30	30	2	10	1720
390	C	CT79	CT79 SMD	-64	+17,5	+20	44	25	2	15	1800
680	D	CT79	CT79 SMD	-80	+25	+25	42	20	3	16	2487
750	D	CT79	CT79 SMD	-80	+25	+25	50	23	3	16	2487
820	D	CT79	CT79 SMD	-80	+25	+25	53	22	3	16	2360
<b>Rated voltage (+85°C) 15 V - 16 V - Category voltage (+125°C) 10 V</b>											
15	A	CT79	CT79 SMD	-24	+10,5	+12	5	155	1	2	780
33	A	CT79	CT79 SMD	-28	+14	+16	10	90	1	2	820
70	B	CT79	CT79 SMD	-28	+14	+16	13	75	1	4	1150
120	B	CT79	CT79 SMD	-28	+14	+16	18	50	1	7	1450
170	C	CT79	CT79 SMD	-32	+14	+16	25	35	2	10	1480
220	C	CT79	CT79 SMD	-41	+13	+15	21	40	2	6	1490
270	C	CT79	CT79 SMD	-56	+17,5	+20	32	30	2	14	1740
330	C	CT79	CT79 SMD	-58	+18	+20	40	30	2	14	1760
470	D	CT79	CT79 SMD	-75	+25	+25	33	24	3	18	2100
540	D	CT79	CT79 SMD	-80	+25	+25	40	23	3	18	2300
560	D	CT79	CT79 SMD	-80	+25	+25	36	23	3	18	2300
<b>Rated voltage (+85°C) 25 V - Category voltage (+125°C) 16 V</b>											
10	A	CT79	CT79 SMD	-16	+8	+9	4	220	1	2	715
22	A	CT79	CT79 SMD	-20	+10	+12	6,6	140	1	2	825
50	B	CT79	CT79 SMD	-28	+13	+15	11	70	1	2	1130
100	B	CT79	CT79 SMD	-28	+13	+15	15	50	1	9	1435
120	C	CT79	CT79 SMD	-32	+13	+15	21	38	2	6	1450
180	C	CT79	CT79 SMD	-48	+13	+15	26	32	2	13	1700
330	D	CT79	CT79 SMD	-60	+25	+25	28	27	3	20	2000
350	D	CT79	CT79 SMD	-64	+25	+25	35	24	3	20	2246
390	D	CT79	CT79 SMD	-68	+25	+25	32	24	3	20	2025
560	D	CT79	CT79 SMD	-65	+25	+30	46	15	9	36	2040
<b>Rated voltage (+85°C) 30 V - Category voltage (+125°C) 20 V</b>											
8	A	CT79	CT79 SMD	-16	+8	+12	4	275	1	2	640
15	A	CT79	CT79 SMD	-20	+10	+12	5	175	1	2	780
40	B	CT79	CT79 SMD	-24	+10,5	+12	10	65	1	5	1120
68	B	CT79	CT79 SMD	-24	+13	+15	13	60	1	8	1285
100	C	CT79	CT79 SMD	-28	+10,5	+12	17	40	2	12	1477
150	C	CT79	CT79 SMD	-48	+13	+15	23	35	2	12	1525
300	D	CT79	CT79 SMD	-60	+25	+25	30	25	3	20	2100

(Standard range)

CT79  
CT79 SMD

## STANDARD RATINGS - ELECTRICAL CHARACTERISTICS

Capacitance 100Hz +20°C (µF)	Case (code)	Type	Capacitance maximum change			Max. DF +20°C (%)	Max. Impedance 100Hz -55°C (Ω)	Max. I leak		Irms Max. 40kHz +85°C (mA)	
			-55°C (%)	+85°C (%)	+125°C (%)			+20°C (µA)	+85°C (µA)		
<b>Rated voltage (+85°C) 40 V - Category voltage (+125°C) 25 V</b>											
12	A	CT79	CT79 SMD	-24	+8	+10	6	234	1	2	450
56	B	CT79	CT79 SMD	-28	+13	+15	14	78	1	9	1100
100	C	CT79	CT79 SMD	-40	+13	+15	18	48	2	17	1450
220	D	CT79	CT79 SMD	-55	+23	+23	22	27	3	22	1900
<b>Rated voltage (+85°C) 50 V - Category voltage (+125°C) 30 V</b>											
5	A	CT79	CT79 SMD	-16	+5	+6	3	400	1	2	580
10	A	CT79	CT79 SMD	-20	+8	+9	4	250	1	2	715
25	B	CT79	CT79 SMD	-20	+10,5	+12	8	95	1	5	1065
47	B	CT79	CT79 SMD	-24	+13	+15	11	70	1	9	1215
60	C	CT79	CT79 SMD	-16	+10,5	+12	12	45	2	12	1335
82	C	CT79	CT79 SMD	-32	+13	+15	15	45	2	10	1460
160	D	CT79	CT79 SMD	-50	+23	+23	17	27	3	22	2040
<b>Rated voltage (+85°C) 60 V - 63 V - Category voltage (+125°C) 40 V</b>											
4	A	CT79	CT79 SMD	-16	+5	+6	2,8	550	1	2	525
8,2	A	CT79	CT79 SMD	-20	+8	+9	4	275	1	2	625
20	B	CT79	CT79 SMD	-16	+10,5	+12	+7	105	1	5	1026
39	B	CT79	CT79 SMD	-24	+10	+12	10	90	1	9	1185
50	C	CT79	CT79 SMD	-16	+10,5	+12	10	50	2	12	1341
68	C	CT79	CT79 SMD	-30	+10,5	+12	13	50	2	10	1393
140	D	CT79	CT79 SMD	-40	+20	+20	16	28	3	22	1990
150	D	CT79	CT79 SMD	-40	+20	+20	17	27	3	22	1865
<b>Rated voltage (+85°C) 75 V - 80 V - Category voltage (+125°C) 50 V</b>											
3,5	A	CT79	CT79 SMD	-16	+5	+6	2,5	650	1	2	525
6,8	A	CT79	CT79 SMD	-20	+8	+9	3	300	1	2	610
15	B	CT79	CT79 SMD	-16	+8	+9	6	150	1	5	1000
33	B	CT79	CT79 SMD	-24	+10	+12	10	90	1	9	1079
40	C	CT79	CT79 SMD	-16	+10,5	+12	9	60	2	12	1293
56	C	CT79	CT79 SMD	-28	+10,5	+15	11	60	2	10	1396
68	C	CT79	CT79 SMD	-30	+14	+15	13	50	2	10	1522
100	D	CT79	CT79 SMD	-35	+20	+20	12	36	9	36	1500
110	D	CT79	CT79 SMD	-35	+20	+20	11	29	3	24	1990
120	D	CT79	CT79 SMD	-36	+20	+20	12	28	3	24	1914
150	D	CT79	CT79 SMD	-48	+21	+22	17	30	9	36	1914
<b>Rated voltage (+85°C) 100 V - Category voltage (+125°C) 65 V</b>											
2,5*	A	CT79	CT79 SMD	-16	+7	+8	2	950	1	2	505
4,7	A	CT79	CT79 SMD	-16	+7	+8	3	500	1	2	565
11*	B	CT79	CT79 SMD	-16	+8	+8	5	200	1	4	835
22	B	CT79	CT79 SMD	-16	+7	+8	7,5	100	1	9	1065
30	C	CT79	CT79 SMD	-16	+8	+8	7	80	2	12	1240
33	C	CT79	CT79 SMD	-16	+8	+8	7	93	2	10	1200
39	C	CT79	CT79 SMD	-16	+8	+8	8	90	2	10	1282
43	C	CT79	CT79 SMD	-20	+8	+8	8	70	2	10	1389
47	C	CT79	CT79 SMD	-20	+7	+8	8	70	2	10	1389
68	D	CT79	CT79 SMD	-24	+15	+15	8	42	3	26	1859
82	D	CT79	CT79 SMD	-24	+15	+15	10	39	3	24	1859
86	D	CT79	CT79 SMD	-24	+15	+15	10	30	3	24	1859
<b>Rated voltage (+85°C) 125 V - Category voltage (+125°C) 85 V</b>											
1,7*	A	CT79	CT79 SMD	-16	+7	+8	2	1250	1	2	415
2,2	A	CT79	CT79 SMD	-16	+7	+8	2	1250	1	2	452
2,7	A	CT79	CT79 SMD	-16	+7	+8	3	780	1	2	452
3,3	A	CT79	CT79 SMD	-16	+7	+8	3	600	1	2	495
3,6	A	CT79	CT79 SMD	-16	+7	+8	2,7	600	1	2	520
3,9	A	CT79	CT79 SMD	-16	+7	+8	3,5	557	1	2	495
9*	B	CT79	CT79 SMD	-16	+7	+8	5	240	1	5	755
14	B	CT79	CT79 SMD	-16	+7	+8	6	167	1	7	1050
15	B	CT79	CT79 SMD	-16	+7	+8	6	167	1	7	1050
18*	C	CT79	CT79 SMD	-16	+7	+8	5	129	2	9	1130
25	C	CT79	CT79 SMD	-16	+7	+8	6	93	2	10	1335
27	C	CT79	CT79 SMD	-16	+7	+8	6	106	2	13	1282
56	D	CT79	CT79 SMD	-25	+15	+15	6	32	3	28	1859

# CT79E

## CT79E SMD

(Extended range)

### STANDARD RATINGS - ELECTRICAL CHARACTERISTICS

Capacitance 100Hz +20°C ( $\mu$ F)	Case (code)	Type		Capacitance maximum change			Max. DF +20°C (%)	Max. Impedance 100Hz -55°C ( $\Omega$ )	Max. I leak		I <sub>rms</sub> Max. 40kHz +85°C (mA)
				-55°C (%)	+85°C (%)	+125°C (%)			+20°C ( $\mu$ A)	+85°C ( $\mu$ A)	
<b>Rated voltage (+85°C) 6 V - 6,3 V - Category voltage (+125°C) 4 V</b>											
120	A	CT79E	CT79E SMD	-41	+15	+16	21	81	1,5	3	820
150	A	CT79E	CT79E SMD	-42	+16	+16	34	80	2	9	820
160	A	CT79E	CT79E SMD	-42	+16	+16	41	80	2	9	820
220*	A	CT79E	CT79E SMD	-64	+13	+16	50	36	2	9	1000
470	B	CT79E	CT79E SMD	-60	+20	+20	90	46	2	10	1281
560	B	CT79E	CT79E SMD	-68	+20	+20	106	48	2	10	1255
820*	B	CT79E	CT79E SMD	-88	+16	+20	155	18	3	14	1500
1500	C	CT79E	CT79E SMD	-90	+20	+25	172	18	5	20	1900
2200	D	CT79E	CT79E SMD	-90	+25	+25	170	13	6	24	2300
<b>Rated voltage (+85°C) 8 V - Category voltage (+125°C) 5 V</b>											
120	A	CT79E	CT79E SMD	-44	+17,5	+20	32	80	2	6	820
180*	A	CT79E	CT79E SMD	-60	+13	+16	41	45	2	9	1000
430	B	CT79E	CT79E SMD	-64	+17,5	+20	64	54	2	10	1230
680*	B	CT79E	CT79E SMD	-83	+16	+20	130	22	3	14	1500
1500*	C	CT79E	CT79E SMD	-90	+20	+25	170	18	5	20	1900
1800*	D	CT79E	CT79E SMD	-90	+25	+30	138	14	7	25	2300
<b>Rated voltage (+85°C) 10 V - Category voltage (+125°C) 6,3 V</b>											
68	A	CT79E	CT79E SMD	-40	+15	+16	21	85	1,5	3	820
82	A	CT79E	CT79E SMD	-40	+16	+16	25	84	2	6	820
100	A	CT79E	CT79E SMD	-40	+16	+16	30	82	2	6	820
150*	A	CT79E	CT79E SMD	-55	+13	+13	34	54	2	9	900
300	B	CT79E	CT79E SMD	-54	+16	+18	60	52	2	10	1195
330	B	CT79E	CT79E SMD	-54	+17	+18	65	52	2	10	1195
350	B	CT79E	CT79E SMD	-60	+18	+18	68	52	2	10	1195
390	B	CT79E	CT79E SMD	-60	+19	+20	74	54	2	10	1195
470	C	CT79E	CT79E SMD	-65	+18	+20	44	25	2	15	1800
560*	B	CT79E	CT79E SMD	-77	+16	+20	106	27	3	16	1450
850	C	CT79E	CT79E SMD	-84	+25	+25	111	36	4	16	1720
1000	C	CT79E	CT79E SMD	-80	+25	+25	92	36	4	16	1720
1200	C	CT79E	CT79E SMD	-80	+20	+25	137	18	5	20	1850
1500	D	CT79E	CT79E SMD	-88	+25	+30	114	15	7	25	2360
1800	D	CT79E	CT79E SMD	-88	+30	+30	138	24	7	25	2360
2200*	D	CT79E	CT79E SMD	-88	+30	+30	170	22	8	26	2360
<b>Rated voltage (+85°C) 15 V - 16 V - Category voltage (+125°C) 10 V</b>											
47	A	CT79E	CT79E SMD	-28	+16	+16	20	100	1,5	3	760
56	A	CT79E	CT79E SMD	-28	+16	+16	22	100	1,5	3	760
82*	A	CT79E	CT79E SMD	-35	+12	+16	20	43	2	6	915
100*	A	CT79E	CT79E SMD	-44	+13	+16	30	72	2	9	900
220	B	CT79E	CT79E SMD	-35	+16	+16	42	62	2	10	1215
270	B	CT79E	CT79E SMD	-45	+18	+18	55	60	2	12	1215
290	B	CT79E	CT79E SMD	-54	+18	+18	60	65	2	12	1215
330	C	CT79E	CT79E SMD	-58	+18	+20	40	30	2	14	1760
390*	B	CT79E	CT79E SMD	-66	+16	+20	74	31	3	16	1450
680	C	CT79E	CT79E SMD	-80	+25	+25	80	42	5	20	1582
750	C	CT79E	CT79E SMD	-80	+25	+25	95	42	6	24	1582
820	C	CT79E	CT79E SMD	-77	+20	+25	95	22	6	24	1800
850	D	CT79E	CT79E SMD	-80	+25	+25	95	24	8	32	2300
1000	D	CT79E	CT79E SMD	-77	+25	+25	92	17	8	32	2300
1200	D	CT79E	CT79E SMD	-84	+25	+30	103	25	8	32	2300

\* out of CECC range

(Extended range)

# CT79E

## CT79E SMD

## STANDARD RATINGS - ELECTRICAL CHARACTERISTICS

Capacitance 100Hz +20°C ( $\mu$ F)	Case (code)	Type	Capacitance maximum change			Max. DF +20°C (%)	Max. Impedance 100Hz -55°C ( $\Omega$ )	Max. I leak		Irms Max. 40kHz +85°C (mA)	
			-55°C (%)	+85°C (%)	+125°C (%)			+20°C ( $\mu$ A)	+85°C ( $\mu$ A)		
<b>Rated voltage [+85°C] 25 V - Category voltage [+125°C] 16 V</b>											
27	A	CT79E	CT79E SMD	-20	+12	+12	11	140	1,5	3	715
33	A	CT79E	CT79E SMD	-24	+14	+14	13	130	1,5	3	715
39	A	CT79E	CT79E SMD	-28	+16	+16	16	120	2	9	715
43	A	CT79E	CT79E SMD	-28	+16	+16	18	120	2	9	715
68*	A	CT79E	CT79E SMD	-40	+12	+15	22	90	2	9	850
150	B	CT79E	CT79E SMD	-35	+15	+15	32	62	2	10	1130
160	B	CT79E	CT79E SMD	-35	+15	+15	34	60	2	10	1130
180	B	CT79E	CT79E SMD	-48	+14	+15	34	60	2	10	1130
220	C	CT79E	CT79E SMD	-52	+18	+20	33	33	2	13	1614
270*	B	CT79E	CT79E SMD	-62	+13	+16	55	33	2	16	1400
390	C	CT79E	CT79E SMD	-70	+25	+25	48	48	7	28	1396
470	C	CT79E	CT79E SMD	-76	+25	+25	48	48	7	28	1398
540*	C	CT79E	CT79E SMD	-80	+25	+25	60	48	7	28	1398
560	C	CT79E	CT79E SMD	-72	+20	+25	60	24	7	28	1750
680	D	CT79E	CT79E SMD	-72	+25	+25	60	19	8	32	2100
820	D	CT79E	CT79E SMD	-80	+25	+25	82	26	8	32	1862
850	D	CT79E	CT79E SMD	-80	+25	+25	95	26	8	32	1970
<b>Rated voltage [+85°C] 30 V - Category voltage [+125°C] 20 V</b>											
25	A	CT79E	CT79E SMD	-24	+12	+12	11	160	1,5	3	640
33	A	CT79E	CT79E SMD	-30	+12	+14	12	160	2	9	640
47*	A	CT79E	CT79E SMD	-23	+12	+15	20	57	2	6	830
56*	A	CT79E	CT79E SMD	-38	+12	+15	22	100	2	9	800
120	B	CT79E	CT79E SMD	-32	+15	+15	30	60	2	10	1185
150	B	CT79E	CT79E SMD	-35	+15	+15	32	60	2	10	1185
170	B	CT79E	CT79E SMD	-48	+15	+15	34	65	2	12	1185
220*	B	CT79E	CT79E SMD	-60	+13	+16	42	36	3	16	1200
300	C	CT79E	CT79E SMD	-60	+15	+15	43	44	6	24	1559
330	C	CT79E	CT79E SMD	-65	+25	+25	45	52	6	24	1373
350	C	CT79E	CT79E SMD	-70	+25	+25	48	52	8	32	1477
390	C	CT79E	CT79E SMD	-75	+25	+25	55	52	8	32	1477
430	C	CT79E	CT79E SMD	-80	+25	+25	60	54	8	32	1477
470*	C	CT79E	CT79E SMD	-65	+20	+25	64	25	8	32	1500
560	D	CT79E	CT79E SMD	-65	+25	+30	40	20	9	36	2000
<b>Rated voltage [+85°C] 40 V - Category voltage [+125°C] 25 V</b>											
15	A	CT79E	CT79E SMD	-20	+10	+12	7	140	1	2	660
18	A	CT79E	CT79E SMD	-20	+12	+12	10	200	1,5	4	580
22	A	CT79E	CT79E SMD	-24	+12	+12	11	190	1,5	4	580
33*	A	CT79E	CT79E SMD	-20	+10	+12	12	88	3	8	795
68	B	CT79E	CT79E SMD	-24	+13	+15	15	60	1	8	1285
100	B	CT79E	CT79E SMD	-40	+15	+15	25	60	2	10	1285
120	B	CT79E	CT79E SMD	-32	+15	+15	30	62	2	12	1241
150	C	CT79E	CT79E SMD	-48	+14	+15	23	35	2	12	1525
270	C	CT79E	CT79E SMD	-60	+25	+25	37	52	7	28	1373
330	C	CT79E	CT79E SMD	-65	+25	+25	43	52	8	32	1373
390	D	CT79E	CT79E SMD	-75	+25	+25	43	30	8	32	1900
470	D	CT79E	CT79E SMD	-80	+25	+25	45	30	9	36	1900
<b>Rated voltage [+85°C] 50 V - Category voltage [+125°C] 30 V</b>											
18	A	CT79E	CT79E SMD	-24	+12	+12	10	200	1,5	3	580
22	A	CT79E	CT79E SMD	-24	+12	+12	11	190	2	9	580
33*	A	CT79E	CT79E SMD	-29	+10	+12	12	135	2	9	700
100	B	CT79E	CT79E SMD	-40	+15	+15	25	67	3	15	1150
120*	B	CT79E	CT79E SMD	-42	+12	+15	22,5	49	4	24	1200
270	C	CT79E	CT79E SMD	-46	+20	+25	37	29	8	32	1450
330*	D	CT79E	CT79E SMD	-46	+25	+30	38	22	9	36	1900
350	D	CT79E	CT79E SMD	-70	+25	+25	40	30	9	36	1900
390	D	CT79E	CT79E SMD	-75	+25	+25	43	30	9	36	1900
430	D	CT79E	CT79E SMD	-80	+25	+25	45	31	10	40	1900

\* out of CECC range

# CT79E

## CT79E SMD

(Extended range)

### STANDARD RATINGS - ELECTRICAL CHARACTERISTICS

Capacitance 100Hz +20°C ( $\mu$ F)	Case (code)	Type	Capacitance maximum change			Max. DF +20°C (%)	Max. Impedance 100Hz -55°C ( $\Omega$ )	Max. I leak		I <sub>rms</sub> Max. 40kHz +85°C (mA)	
			-55°C (%)	+85°C (%)	+125°C (%)			+20°C ( $\mu$ A)	+85°C ( $\mu$ A)		
<b>Rated voltage (+85°C) 60 V - 63 V - Category voltage (+125°C) 40 V</b>											
10	A	CT79E	CT79E SMD	-20	+8	+9	4	250	1	2	572
12	A	CT79E	CT79E SMD	-20	+8	+9	7	233	2	4	572
15	A	CT79E	CT79E SMD	-22	+9	+9	8	220	2	9	562
27*	A	CT79E	CT79E SMD	-24	+10	+12	10	144	3	12	700
47	B	CT79E	CT79E SMD	-24	+13	+15	13	70	1	9	1150
56	B	CT79E	CT79E SMD	-26	+14	+15	18	72	2	12	1150
82	B	CT79E	CT79E SMD	-36	+15	+15	22	70	2	12	1150
100*	B	CT79E	CT79E SMD	-36	+12	+15	19	54	4	20	1100
100	C	CT79E	CT79E SMD	-37	+14	+15	18	42	2	11	1420
120	C	CT79E	CT79E SMD	-40	+18	+18	20	49	3	18	1420
220	C	CT79E	CT79E SMD	-40	+16	+20	30	29	8	32	1400
270	D	CT79E	CT79E SMD	-45	+20	+25	26	23	9	36	1850
330	D	CT79E	CT79E SMD	-72	+25	+25	32	31	10	40	1850
<b>Rated voltage (+85°C) 75 V - 80 V - Category voltage (+125°C) 50 V</b>											
8,2	A	CT79E	CT79E SMD	-22	+9	+9	6	280	1,5	3	610
9	A	CT79E	CT79E SMD	-22	+9	+9	6	280	2	4	572
22*	A	CT79E	CT79E SMD	-19	+10	+12	8,5	157	3	12	600
43	B	CT79E	CT79E SMD	-24	+10,5	+12	15	89	2	10	1051
47	B	CT79E	CT79E SMD	-30	+14	+14	15	87	2	10	1051
56	B	CT79E	CT79E SMD	-28	+10,5	+15	11	72	2	12	1051
68	B	CT79E	CT79E SMD	-36	+15	+15	21	86	2	12	1051
82*	B	CT79E	CT79E SMD	-30	+12	+15	15	63	4	24	1000
82	C	CT79E	CT79E SMD	-32	+14	+15	15	45	2	10	1335
100	C	CT79E	CT79E SMD	-36	+17	+18	19	60	8	32	1335
150	C	CT79E	CT79E SMD	-40	+20	+20	25	60	9	36	1335
180	C	CT79E	CT79E SMD	-35	+16	+20	28	30	9	36	1335
220	D	CT79E	CT79E SMD	-40	+20	+22	24,4	24	10	40	1850
250	D	CT79E	CT79E SMD	-68	+25	+25	40	33	10	40	1850
270*	D	CT79E	CT79E SMD	-68	+25	+25	42	35	11	44	1850
<b>Rated voltage (+85°C) 100 V - Category voltage (+125°C) 65 V</b>											
5,6	A	CT79E	CT79E SMD	-17	+8	+8	6	475	2	5	530
10*	A	CT79E	CT79E SMD	-17	+10	+12	4,5	200	3	12	800
30	B	CT79E	CT79E SMD	-16	+8	+8	10	99	3	15	1065
33	B	CT79E	CT79E SMD	-16	+8	+8	14	95	3	15	1065
39	B	CT79E	CT79E SMD	-20	+12	+12	10	80	2	12	1300
56	C	CT79E	CT79E SMD	-28	+14	+15	11	60	2	10	1335
68	C	CT79E	CT79E SMD	-30	+14	+15	11,3	40	10	40	1600
100	D	CT79E	CT79E SMD	-35	+20	+20	11	36	3	24	1859
120*	D	CT79E	CT79E SMD	-35	+15	+17	25	30	12	48	2000
<b>Rated voltage (+85°C) 125 V - Category voltage (+125°C) 85 V</b>											
6,8*	A	CT79E	CT79E SMD	-14	+10	+12	6	300	3	12	700
18	B	CT79E	CT79E SMD	-16	+8	+8	8	133	2	10	1065
27*	B	CT79E	CT79E SMD	-18	+12	+15	7,2	90	5	24	1200
39	C	CT79E	CT79E SMD	-16	+8	+8	8	90	2	10	1282
47	C	CT79E	CT79E SMD	-23	+10	+10	7,9	50	2	10	1500
68	D	CT79E	CT79E SMD	-24	+15	+15	8	42	3	26	1859
82	D	CT79E	CT79E SMD	-24	+15	+17	10	32	3	24	1900
<b>Rated voltage (+85°C) 150 V - Category voltage (+125°C) 100 V</b>											
2,5*	A	CT79E	CT79E SMD	-16	+8	+8	3	780	1	3	495
3,3*	A	CT79E	CT79E SMD	-16	+8	+8	3	600	1	3	495
14*	B	CT79E	CT79E SMD	-16	+8	+8	10	167	2	10	1065
18*	B	CT79E	CT79E SMD	-16	+8	+8	10	133	2	10	1065
25*	C	CT79E	CT79E SMD	-16	+8	+8	20	93	2	20	1335
47*	C	CT79E	CT79E SMD	-24	+10	+10	20	70	2	20	1335
56*	D	CT79E	CT79E SMD	-24	+15	+15	30	47	3	30	1860
82*	D	CT79E	CT79E SMD	-24	+18	+18	30	39	3	30	1860

\* out of CECC range

# Electrical characteristics

## CAPACITANCE


The capacitance is defined by a rated value ( $C_R$ , indicated on the capacitor) and a tolerance (generally  $\pm 20\%$ ).

The capacitance is measured at a 100Hz or at a 120Hz frequency under a 0,1 to 1  $V_{AC}$  voltage and a 2,1 to 2,5 V bias (or 9 to 10 V for  $U_R \geq 100$  V).

At room temperature, it must be in the range defined by the rated value and the tolerance.

Capacitance change vs temperature: see typical curves below. Maximum changes are given, for each type, on the data sheets.

## CAPACITANCE CHANGE VS TEMPERATURE



## TOLERANCE (ON RATED CAPACITANCE)

It defines, with the rated capacitance, the range in which the capacitance value must be at room temperature.


**e.g.:** Rated capacitance:  $100\mu F$

Tolerance: 20%

The measured capacitance must be between:

$$100 - (20\% \text{ of } 100) = 80\mu F \text{ and } 100 + (20\% \text{ of } 100) = 120\mu F$$

The standard tolerance for tantalum capacitors is 20%.




# Electrical characteristics


## DIRECT DC VOLTAGE

The **rated voltage ( $U_R$ )**, indicated on the capacitor, is the maximum DC voltage which can be applied continuously between  $-55^{\circ}\text{C}$  and  $+85^{\circ}\text{C}$ .

For the types which can be used up to  $125^{\circ}\text{C}$ , the voltage must be derated between  $+85^{\circ}\text{C}$  and  $+125^{\circ}\text{C}$  according to the following curve.



For the types which can be used up to  $200^{\circ}\text{C}$ , the voltage must be derated between  $+85^{\circ}\text{C}$  and  $+200^{\circ}\text{C}$  according to the following curve.



The **category voltage ( $U_c$ )** is consequently the maximum DC voltage which can be applied continuously at  $+125^{\circ}\text{C}$ .

The **surge voltage** is the maximum voltage which can be applied for short periods.

It is given for each type in the data sheet and is generally equal to 1,15 times  $U_R$  between  $-55^{\circ}\text{C}$  and  $+85^{\circ}\text{C}$  and 1,15 times  $U_c$  at  $+125^{\circ}\text{C}$ .

Tests are performed with charging periods of 30 seconds, through a  $1000 \Omega$  resistor, and discharging periods of 5 min 30s. 1000 cycles are done.

## REVERSE VOLTAGE

Capacitors in silver cases (CT4, CT4E, CT9, CT9E) and some in tantalum cases (WT83, WS83) cannot withstand any reverse voltage: it would cause damage, more or less rapidly depending upon the voltage value.

It is therefore necessary to be sure that the bias voltage is high enough to avoid that the AC voltage creates a reverse voltage (negative peak).

Other capacitors in tantalum cases (CT79, CT79E, ST79, DSCC 93026, M39006/22 and M39006/25) can withstand a reverse voltage as specified in the individual datasheet.


## LEAKAGE CURRENT

Leakage current is the residual current which flows through the capacitor after the charging time, under rated voltage. It is measured after a time not exceeding 5 minutes and is given in  $\mu\text{A}$ .

It is equivalent to the insulation resistance of the capacitor and it must be as low as possible.

Maximum leakage current is a function of capacitance and rated voltage values and is given, for each type, in the data sheets.

## LEAKAGE CURRENT CHANGE VS APPLIED VOLTAGE





# Electrical characteristics

## DISSIPATION FACTOR

Dissipation factor is generally measured at the same time as the capacitance, with the same conditions. It is a function of the series resistance of the capacitor and the capacitance at low frequency.


$$DF = ESR \times C \times 2\pi f$$

At low frequency, the series resistance is the sum of an ohmic part (leads, contacts, MnO<sub>2</sub>) and the dielectric losses.

Dissipation factor is given in % and maximum limits are given for each type in the data sheets.

## EQUIVALENT SERIES RESISTANCE OR IMPEDANCE

Equivalent circuit of a capacitor



**R:** equivalent series resistance of the capacitor (leads, contacts, MnO<sub>2</sub>, dielectric losses)

**L:** inductance mainly due to the leads

**C:** capacitance

### Impedance

It is specified at 100Hz and -55°C and the formula for impedance is:


$$Z = \sqrt{R^2 + [L\omega - 1/C\omega]^2}$$

It can be seen that:


- at low frequencies, impedance is a function of capacitance
- at high frequencies, impedance is a function of inductance
- at medium frequencies, it is a function of the ESR

Maximum impedance: see data sheets.

## ESR CHANGE VS TEMPERATURE



## ESR CHANGE VS FREQUENCY



# Electrical characteristics

## MAXIMUM RIPPLE CURRENT

### CT79/79E (SMD) - CT79/79E HT200 - ST79 (SMD) - ST79 HT200 - WT83 - WS83

Maximum ripple currents which are indicated in the data sheets are given for the following conditions:

**Temperature:** +85°C (+70°C only WT82)

**Frequency:** 40kHz

**Applied voltage:** 0,66

If conditions are different, use the multipliers given in the table below to calculate the new maximum current.

Frequency	100Hz				1kHz				10kHz				40kHz				100kHz				
	+55°C	+85°C	+105°C	+125°C	+55°C	+85°C	+105°C	+125°C	+55°C	+85°C	+105°C	+125°C	+55°C	+85°C	+105°C	+125°C	+55°C	+85°C	+105°C	+125°C	
Peak voltage in % of $U_R$	66%	0,6	0,6	0,46	0,27	0,72	0,72	0,55	0,32	0,88	0,88	0,68	0,4	1	1	0,77	0,45	1,1	1,1	0,85	0,5
	70%	0,6	0,58	0,44	–	0,72	0,7	0,52	–	0,88	0,85	0,64	–	1	0,97	0,73	–	1,1	1,07	0,8	–
	80%	0,6	0,52	0,35	–	0,72	0,62	0,42	–	0,88	0,76	0,52	–	1	0,87	0,59	–	1,1	0,96	0,65	–
	90%	0,6	0,46	–	–	0,72	0,55	–	–	0,88	0,67	–	–	1	0,77	–	–	1,1	0,85	–	–
	100%	0,6	0,39	–	–	0,72	0,45	–	–	0,88	0,55	–	–	1	0,63	–	–	1,1	0,69	–	–

### CT4 - CT4E - CT9 - CT9E TYPES

Maximum ripple currents which are indicated in the data sheets are given for the following conditions:

- frequency from 100Hz to 100kHz and more
- temperature from –55°C to +85°C

#### Correction vs temperature

If the temperature is higher than 85°C, decrease linearly the maximum value from 100% at +85°C to 80% at +125°C.

#### Correction vs frequency

If frequency is lower than 100Hz, apply the following multipliers to the maximum ripple currents:

**75Hz:** 0,79      **60Hz:** 0,65      **50Hz:** 0,55      **25Hz:** 0,55

### OTHERS RULES (FOR ALL TYPES)

- the sum of the positive peak AC voltage and the DC bias voltage must be lower than the rated voltage.
- the negative peak must not create any Reverse voltage (or maximum 3 volts for CT79 and CT79E types).
- because of the increase of the series resistance at low temperature, it is better to not apply directly the maximum ripple current but to increase this one gradually to raise the capacitor temperature.

## CLIMATIC CHARACTERISTICS

### 1- CLIMATIC CATEGORY

Climatic category defines the temperature range over which the capacitor can be used continuously, and also the number of days for the damp heat test (this test is performed periodically at 40°C with a 93% moisture rate).

**Note:** it is necessary to derate the voltage for temperatures higher than 85°C (see page 15).

## 2- THERMAL SHOCKS - RAPID CHANGES OF TEMPERATURE

This test is performed to check that the capacitors can withstand sudden temperature changes. The method which is used is the one with two chambers, one at –55°C, the other one at +125°C. Five cycles are performed, with 30min at low temperature and 30min at high temperature, during the periodical tests (30 cycles for CT79 type). Electrical characteristics are measured after this test.

### 3 - DAMP HEAT TEST

This test is performed during the periodical test, with the following conditions:

**Temperature:** 40°C

**Humidity:** 90 to 95%

**DC voltage:** without

**Time:** 21 or 56 days

Electrical characteristics are measured after this test.

## MECHANICAL CHARACTERISTICS

### 1 - VIBRATIONS

This test is performed during the periodical test, with the following conditions:

#### CT9 - CT9E types

- Frequency: 10 to 2000Hz
- Amplitude: 1,5mm or 196m/s<sup>2</sup> - 20g
- Time: 6 hours

#### CT79/79E (SMD) - CT79/79E HT200 - ST79 (SMD) - ST79 HT200 - WT83 - WS83

- Frequency: 10 to 2000Hz
- Amplitude: 3,5mm or 490m/s<sup>2</sup> - 50g
- Time: 6 hours

### 2 - SHOCKS

This test is performed just after the vibrations test, with the following conditions for all types:

- Acceleration: 981 m/s<sup>2</sup> - 100g
- Pulse width: 6 ms
- Shape: 1/2 sinewave
- Number of shocks: 18 (3 in each direction, positive and negative)

# Electrical characteristics

## RELIABILITY

Reliability of a component can be defined as its probability to work without any failure, in defined conditions and during a fixed time.

Reliability is not therefore only a function of the component quality, but also of the application and environmental conditions.

The parameter which is the most commonly used for the reliability is the failure rate in time, generally expressed in % per 1000 hours.

### CALCULATION OF A COMPONENT FAILURE RATE USED IN AN EQUIPMENT

The calculation method on the next page uses parameters which are given by the CNET (Centre National d'Étude des Télécommunications) in its Reliability Data Book (RDF 1993).

The failure rate is calculated with parameters which are function of the capacitor (capacitance, case type, approvals, high surge current test) and others ones which are representative of application conditions (voltage, temperature, resistance in serie, environmental conditions).

#### Example:


CT79E 2200 $\mu$ F - 6,3 V used under 3 volts, at 40°C, in a satellite in orbit:

$$\pi_t = 1,2 \quad \pi_v = 1,38$$

$$\pi_c = 1,4 \quad \pi_E = 0,5 \quad \pi_q = 1$$

$$\lambda = 3 \times 1,2 \times 1,38 \times 1,4 \times 0,5 \times 1.10^{-9}/h = 3,5.10^{-9}/h = 0,00035\% \text{ defects}/1000 \text{ hours}$$


### $\pi_t$ = TEMPERATURE INFLUENCE



$$\text{Formula: } \pi_t = \exp [1,8. (t / tm)^2]$$

with: t = using temperature  
tm = maximum temperature  
Curve for tm = 125°C

### $\pi_v$ = INFLUENCE OF APPLIED VOLTAGE VS RATED VOLTAGE



$$\text{Formula: } \pi_v = \exp [(\rho / 0,85)^2]$$

$$\rho = \frac{\text{peak voltage}}{\text{rated voltage}}$$

Curve  $\pi_v = f(\rho)$

### $\pi_c$ = INFLUENCE OF CAPACITANCE

3,3 $\mu$ F	$\pi_c = 0,9$
20 $\mu$ F	$\pi_c = 1,0$
1000 $\mu$ F	$\pi_c = 1,3$
2200 $\mu$ F	$\pi_c = 1,4$

### $\pi_E$ = INFLUENCE OF APPLICATION

Satellite in orbit	$\pi_E = 0,5$
Ground; stationary; protected	$\pi_E = 1$
Ground; stationary; non protected	$\pi_E = 2,5$
Ground; mobile; soft conditions	$\pi_E = 6$
Aircraft; soft conditions	$\pi_E = 6$
Ship; soft conditions	$\pi_E = 6$
Ground; mobile; hard conditions	$\pi_E = 8$
Ship; hard conditions	$\pi_E = 10$
Aircraft; hard conditions	$\pi_E = 15$
Satellite; launching	$\pi_E = 20$

### $\pi_q$ = INFLUENCE OF QUALIFICATION

Products approved to CECC	$\pi_q = 1,0$
Others products	$\pi_q = 2,0$

# Electrical characteristics

## PRODUCT SAFETY INFORMATION SHEET

This should read in conjunction with the Product Data Sheet/Specification.

Failure to observe the ratings, and the information on this sheet may result in a safety hazard.

### 1. MATERIAL CONTENT

Wet tantalum capacitors contain hazardous materials:

- Liquid electrolyte - gelled diluted sulphuric acid
- Solid tantalum anode

The device consists of solder coated terminal wires and the materials listed below:

- Silver case or tantalum case
- Rubber "o" rings
- PTFE spacers
- Filled epoxy resin end cap on silver case products

### 2. PHYSICAL FORM

These Capacitors are physically small and are cylindrical with axial leads.

### 3. INTRINSIC PROPERTIES

#### 3.1 Operating

Wet tantalum capacitors will operate satisfactorily providing that the sum of the applied d.c. and the peak a.c. ripple voltage does not exceed the rated d.c. voltage.

There must be no reversal of polarity.

The maximum ripple currents and voltages and d.c. polarising voltages are specified in the data sheets.

Some tantalum cased devices will stand up to 3 V<sub>DC</sub> Reverse for short periods of time.

A Reverse application of the rated voltage will result in loss of capacitance, early short circuit failure and may result in fire or explosion.

It may also cause consequential failure of other associated components in circuit, e.g. diodes, transformers, etc.

#### 3.2 Non-Operating

Wet Tantalum capacitors contain electrolyte which is a conducting material.


If electrolyte leaks onto a printed circuit board or similar insulated support, short circuits can be caused.

All electrolytes are corrosive to some extent.

No electrolyte should be allowed to come in contact with the skin, eyes, etc., and if they do appropriate medical treatment should be applied.



## CONSTRUCTION

CT79/79E (SMD) - CT79/79E HT200 - ST79 (SMD) - ST79 HT200 - WT83 - WS83




Glass metal seal: CT9 - CT9E

Epoxy sealing: CT4 - CT4E



## MARKING (except DSCC 93026, M39006/22, M39006/25)



## PACKAGING

In cardboard boxes

# General information

Tantalum capacitors are, with ceramic, aluminum and film capacitors, one of the most used family.

The manufacturing technology and the constant improvements in tantalum powders allow it to be the capacitor with the highest CV (product capacitance x voltage) per volume, very long life and high reliability.

It has also the following advantages:

- Wide range of capacitance (less than 1 $\mu$ F to more than 10 000 $\mu$ F)
- Wide operating temperature range (-55°C to +200°C)
- Electrical characteristics stable with temperature
- Low leakage current
- Very low ESR for some types
- Stability after long periods of storage, without any reforming

All these characteristics allow tantalum capacitors to be commonly used either in large volume markets like mobile phones or computers, or in specific High-Rel applications such as space, aerospace and military.

Its main uses are found in the following functions:

- Filtering
- Bypass
- Coupling
- RC time constant
- Energy storage

Tantalum capacitors can be divided into two main families and several sub-families:

#### Solid tantalum capacitors:

- Solid MnO<sub>2</sub>
  - Metal cases
  - Molded cases
  - SMD
- Solid Polymer
  - SMD

#### Wet tantalum capacitors:

- Silver cases
- Tantalum cases

#### HOW TO USE THE SELECTION GUIDE

- 1 - The **Technical Selection Guide** can be used to select a product according to the main technical requirements.
- 2 - The **Classification according to specification** makes the link between all major standard specifications and the products.
- 3 - The **Selection Guide** by family has the same classification as in the catalogue. You will find for each type the main features, the approvals and the page number of the technical data sheet.

## MANUFACTURING

### ANODE AND INSULATOR

Tantalum capacitors are the capacitors which have the highest ratio of capacitance per volume. This is mainly due to the high dielectric coefficient of its insulator and to its large cross-section.

The basic raw material is a high purity (greater than 99,99%) tantalum powder with a very fine granulation, compressed to form a cylinder or a parallelepiped constituting the anode of the capacitor (positive plate).

The pellet is then sintered at high temperature (1200°C to 2200°C), under high vacuum (10<sup>-6</sup> Torr), firstly to purify the powder and secondly to obtain a strong mechanical structure by a welding of the particles.

The insulating part is obtained by anodization to a depth of the tantalum surface which forms a tantalum pentoxide film (Ta<sub>2</sub>O<sub>5</sub>) with a thickness of about 16 angstroms per anodization volt. The dielectric coefficient is between 21 and 27 depending upon the anodization conditions.

### WET ELECTROLYTE: CATHODE AND ENCAPSULATION

In this case, the cathode is formed by a sulphuric acid solution. The anodized tantalum pellet is impregnated with this solution and then placed in a silver or tantalum case, into which some equivalent gelled solution have been previously deposited.

The case is then crimped on the internal PTFE gasket to make the sealing. The final steps are welding (CT79), soldering (CT9) or elastomer seal (CT4) depending on the capacitors.

### SOLID ELECTROLYTE: CATHODE AND ENCAPSULATION

In this case, the cathode is formed either by manganous dioxide which is a grey semi conductor or by polymer solution.

Solid MnO<sub>2</sub> cathode is obtained by dipping the pellets into a manganous nitrate water solution which impregnates the internal structure; this solution is then decomposed in a high temperature oven to obtain manganous dioxide. This operation is repeated several times. The nature and quality of this semiconductor are important to some of the electrical parameters (especially the serial resistance).

To finish the negative plate, a graphite coating and then a silver coating are deposited on the outside surface of the manganous dioxide or conducting polymer.

The positive nickel lead is welded on the tantalum wire and the negative lead is either soldered for the products with axial leads or glued with a silver epoxy for the SMD range.

### BURN-IN - SORTING - INSPECTION

All the products are submitted to a final burn-in, with differing severities depending upon the characteristics of each type (temperature, voltage, duration).

Then follows the sorting, marking and inspection operations. It can be noted that the procedures for these operations are the same for approved and non approved parts (except the periodical tests).

# General information

## TYPE IDENTIFICATION - ORDERING INFORMATION

### THE COMPLETE IDENTIFICATION OF A PRODUCT IS MADE OF

- The type (or model)
- The tolerance
- The case size
- The rated voltage
- The rated capacitance
- If applicable the CECC specification number

### THE TYPE

It can be expressed with the commercial description (CTC21E C 33 $\mu$ F 10% 40V) or the **EXXELIA** part number (TS22EC336K040F).

When applicable the CECC specification number should be indicated.

### THE CASE SIZE

It is indicated on the technical data sheets in front of each capacitance-voltage value and is generally identified by a letter code. It is important to give this information because there can be, for the same type, a standard range and an extended range in which the same value will be available in two different sizes.

### THE RATED CAPACITANCE

It can be expressed:

- Directly in  $\mu$ F (eg: 47 $\mu$ F)
- Coded according to MIL specification, with:
  - 2 digits number for the value
  - A multiplying factor to obtain the capacitance in pF (power of 10)

**Eg:** 567 = 56.10<sup>7</sup> pF = 560 $\mu$ F

### THE TOLERANCE

It can be expressed directly in % or identified by a code letter:

M =  $\pm$ 20%

K =  $\pm$ 10%

J =  $\pm$ 5%

**N.B.:** the standard tolerance for tantalum capacitors is 20%; if no tolerance is specified, it would be considered as 20%.

A 20% tolerance means in fact -20% to +20%.

### THE RATED VOLTAGE

It is expressed directly in volts (V)

**N.B.:** 6,3V rated voltage can be coded as 6V.

## CECC SPECIFICATIONS

Some of the products which are described in this catalogue are made to a CECC specification; these documents give in detail the following information for each type:

- The climatic, electrical and mechanical characteristics
- The test and inspection procedures
- The sampling methods and levels
- The tests periods

The reference specifications concerning the tantalum capacitors are the following:

### CECC 30 000 (NFC 83-100)

Generic specification: fixed capacitors

- Terminology
- Quality Assessment Procedures
- Test and inspection methods

### CECC 30 200 (NFC 83-112)

Sectional specification: tantalum capacitors

- Preferred characteristics
- Quality Assessment Procedures
- Test and inspection methods

### CECC 30 201 XXX

Detail specifications solid tantalum capacitors

- Detailed characteristics for each type

### CECC 30 202 XXX

Detail specifications wet tantalum capacitors

- Detailed characteristics for each type

### CECC 30 800 (NFC 83-113)

Sectional specification: tantalum chip capacitors

- Preferred characteristics
- Quality Assessment Procedures
- Test and inspection methods

### CECC 30 801 XXX

Detail specifications tantalum chip capacitors

- Detailed characteristics for each type
- The list of all the detail specifications is given in the selection guide, with the corresponding type.

**NB:** Some of the products refer to specifications which are no longer published.

## OTHER SPECIFICATIONS

In addition to CECC approvals, some of the products are qualified to MIL standard M39006/22, M39006/25, DSCC DWG No. 93026 and some others are listed in ESA (European Space Agency) Preferred Parts Lists ESCC EPPL I or II.